Het Nationale Theater

Theater aan het Spui

Technical rider Small stage/Zaal 2.

Version: Januari 2023

General

Theatre Black box

Tribune Telescopic tribune (retractable)

Total seats 160

Stage floor A wooden sprung floor with floor heating

Dimensions stage (in meters)

Width 11,00 from wall to wall

10,20 between side masking

Depth 9,00 from tribune to rear wall

8,10 from tribune to backdrop 7,50 from 0-point to rear wall 6,60 from 0-point to backdrop

16,00 retracted tribune to rear wall

Free height 5,40 from floor to lighting bridge

7,65 between lighting bridges (till fly-bars)

2,20 doors loading dock

Masking

Side masking (black, ruffed)

Backdrop (black, ruffed)

In rail, under lighting bridge

In rail, under lighting bridge

Legs (black, ruffed) Max. 1 set

Opening between 2,60 – 9,00 meters

Borders (black, ruffed) 1x 11,00x2,85 meters

2x 11,00x1,85 meters

Cyclorama (white) 1x 7,30x6,00 meters

1x 10,50x5,60 meters

Gauze (black) No Front curtain No

Marley floor Black/Grey. Covers the entire stage

Fly facilities

Max. load pipe end

Number of bars 14

Control Varicon Length of the bar 8,00 meters Max. height 7,65 meters Max. load 250 kg Max. load under steelcable 150 kg Max. Load between steelcables 100 kg

Side bars 1 left and 1 right

5,50 meter Max. height Max. load 250 kg Max. load under steelcable 150 kg Max. load between steelcable 100 kg Max. load pipe end 35 kg

Check the ground plan (Bruggenplan) for specifications

Light

GrandMA3 onPC command wing XT Lighting console

Dimmers ETC 78 (3 kW) on the bridges 4 (5 kW) on the bridges

40 on multi-core on the bridges

16 (2,5 kW) on the floor

35 kg

Sockets CEE form

Follow spot

40x Selecon pacific 23-50 incl. iris. 800 W. **Bridges**

> 18x ADB Fresnel F101 with barndoor 1kW 20x PAR64 230V, 1kW CP62 medium 20x Par64 230V, 1kW CP61 narrow

Additional 20x Selecon pacific 23-50 incl. iris. 800W

> 6x 4-bar Par64 230V, 1KW CP62 medium* 6x 4-bar Par64 230V, 1KW CP61 narrow*

Cyclorama lights 3x. Each 4x 1kW Theatro Deluvio 1000

Sound

FOH

L&R Each side 2x d&b Y7P (hang)

Centre No

Sub2x d&b V-SUBSurround2x PL Audio F8Additional speakers2x d&b Y7P

Stage monitor 2x d&b MAX15

Mixers Avid S3L-X incl. Stage-rack 32 channels

Additional 2x CD player Denon*

Microphones and stands On request

FOH multi-core 3x 12 channel: Left and right down & Left up stage

Video

Projector Eiki EK-800U 12.000 Ansi lumen

Lens: 2.00 – 4.00

Projection screen 16:10; 6,30 x 4,01 meter*

16:10; 4,47 x 2,87 meter*

Power current

Socket (CEE-red) Upper-left 1x 32A (sound)

Backstage 1x 125A*, 1x 63A*

FOH 1x 32A

On the bridges 4x 16A

Additional

Grand piano Schimmel 208 T, black*
Piano Yamaha U3, black*

Personnel lift ALP AMWP9.5-1100, max work height 9,50m*

Alp AWP 12-1000, max work height 12,00m*

Intercom ASL intercom. 4x belt pack (wired)*

Hazers Martin JEM K1, DMX*

DF-50*

Smoke machine Martin JEM ZR45, DMX*

Stage decks 6x 2x1m. All stage decks have 20,40,60,80 and 100 cm

legs

Dressing rooms 1x 3 persons with shower and toilet

1x 8 persons with shower and toilet

Contact en information

 General
 receptie@hnt.nl
 +31(0)88 356 53 56

 Box office
 kassaspui@hnt.nl
 +31(0)88 356 53 56

Website <u>www.hnt.nl</u>

Technical manager djurrevandevlekkert@hnt.nl +31(0)88 356 52 43

Address

Theater aan het Spui Spui 187 2511 BN Den Haag

Loading dock

Address: Kranestraat 10, 2512 AE Den Haag.

Pay attention! Big trucks should be driving backwards into the Kranestraat, from the Amsterdamse Veerkade.

Each stage has one loading dock. It's possible to leave your truck there during your stay. Length loading dock: 20 meters.

Loading platform is 0,90 meters high from street level. Doors to main stage/zaal 1 are 2,20 x 2,40 meters (wxh).

Doors to small stage/zaal 2 are 2,20 x 2,17 meters(wxh).

* This equipment is used for main stage, small stage and auditorium. Please ask in advance for it's availability.