

Theater aan het Spui

Technical rider Main stage/Zaal 1.

Version: November 2017.

General

Theatre	Black box
Tribune	Telescopic tribune (retractable)
Total seats	346
Stage floor	A wooden sprung floor with floor heating

Dimensions stage (in meters)

Width	18,00 from wall to wall
	17,72 between side masking
	16,52 between side masking
Depth	13,00 from tribune to rear wall
	12,90 from tribune to backdrop
	12,50 from 0-point to rear wall
	11,90 from 0-point to backdrop
	23,00 retracted tribune to rear wall
Free height	7,00 from floor to lighting bridge
	8,50 between lighting bridges (till fly-bars)
	2,40 doors loading dock

Masking

Side masking (black, ruffed)	In rail, under lighting bridges
Backdrop (black, ruffed)	In rail, against the back wall
Legs (black, ruffed)	Max. 5 sets
Borders (black, ruffed)	2x 15,00x3,00 meters
	1x 15,00x1,80 meters
Cyclorama (white)	13,60x7,30 meters
Gauze (black)	13,60x7,30 meters
Front curtain	No
Marley floor	Black/Grey. Covers the entire stage

Fly facilities

Number of bars	12
Control	Artcom
Length of the bar	15,00 meters
Max. height	8,50 meters
Max. load	300 kg
Max. load under steelcable	150 kg
Max. load between steelcables	200 kg
Max. load pipe end	50 kg
Side bars	1 left and 1 right
Max. height	7,00 meters
Max. load	300 kg
Max. load under steelcable	150 kg
Max. load between steelcables	200 kg
Max. load pipe end	50 kg

Check the ground plan (Bruggenplan) for specifications

The flybars and bridges are movable. Ask the technical manager for more information.

Light

Lighting console	ETC Ion with Wing
Dimmers ETC	36 (2,5 kW) on the bridges 12 (5 kW) on the bridges 168 (3 kW) on multi-core 40 (2,5 kW) on the floor
Sockets	CEE form
Follow spot	No
FOH bar (fixed)	24x Selecon Pacific 23-50 incl. Diafragma. 80V 1200W
Additional	12x ADB Fresnel C201/F with barndoor 2kW 20x PAR64 230V, 1kW CP62 medium 20x Par64 230V, 1kW CP61 narrow 70x Selecon pacific 23-50 incl. iris. 800 W
Cyclorama lights	4x. Each 4x 1kW Theatro Deluvio 1000

Sound

FOH

L&R

Each side 2x d&b C7 (hang)

Centre

4x d&b MAX15

Sub

4x C7 (hang)

Front fills

2x d&b MAX15

Surround

2x PL Audio F10

Stage monitor

4x d&b MAX15

Mixers

Avid SC-48

Yamaha o1v96*

Additional

BSS Soundweb London

2x CD player Denon*

Microphones and stands

On request

FOH multi-core

4x 12 channel: Left and right, up and down stage

Video

Projector

Eiki EK-800U 12000 Ansi lumens

Lens: 2.00 – 4.00

Projection screen

16:9; 6,30 x 3,54 meters*

Power current

Socket (CEE-red)

Upper-left 1x 32A (sound), 1x 63A (sound)
Upper-right 1x 63A
Backstage 1x 125A*, 1x 63A*
FOH 1x 32A
On the bridges 3x 32A, 4x 16A

Additional

Grand piano
Piano

Schimmel 208 T, black*
Yamaha U3, black*

Personnel lift

Novon AMWP7.5 1000, max platform height
7,50m*
Alp PHCI 940, max platform height 9,40m*

Intercom

ASL intercom. 4x belt pack (wired)*

Hazers

Martin JEM K1, DMX*
DF-50*

Dressing rooms

5x 4 persons with shower and toilet
1x 4 persons without shower and toilet

Contact and information

General	receptie@hnt.nl	+31(0)70 356 53 56
Box office	kassaspui@hnt.nl	+31(0)70 346 52 72
Website	www.hnt.nl	
Technical manager	djurrevandevlekkert@hnt.nl	+31(0)70 318 14 84

Address

Theater aan het Spui
Spui 187
2511 BN Den Haag

Loading dock

Address: Kranestraat 10, 2512 AE Den Haag.

Pay attention! Big trucks should be driving backwards into the Kranestraat, from the Amsterdamse Veerkade.

Each stage has one loading dock. It's possible to leave your truck there during your stay.

Length loading dock: 20 meters.

Loading platform is 0,90 meters high from street level.

Doors to main stage/zaal 1 are 2,20 x 2,40 meters (wxh).

Doors to small stage/zaal 2 are 2,20 x 2,17 meters(wxh).

* This equipment is used for main stage, small stage and auditorium. Please ask in advance for it's availability.